

SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015



Date Issued : 04/25/2018

SDS No : Rust Check Rust Inhibitor aerosol - 1043 180g_ENG

Date Revised : 11/18/2019

Revision No : 3

1043 RUST CHECK RUST INHIBITOR, aerosol

1. IDENTIFICATION

Product Name: 1043 RUST CHECK RUST INHIBITOR, aerosol

Product Description: Lubricant / rust preventive, oil-based 180 g / 6.35 oz

General Use: Rust Preventative Lubricant, aerosol

Product Stock/Code: 1043

Chemical Family: Hydrocarbon oil, solvent-based

Molecular Formula: Mixture

Manufacturer / Supplier

Rust Check Corporation
6175 Danville Road, Mississauga
Ontario, Canada L5T 2H7

Customer Service: 905-670-5411

Emergency Telephone Numbers (24 hour)

CANUTEC : (613) 996-6666

CHEMTREC : (800) 424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2012) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2015). This information may be different from the actual product label information for labels that are regulated by other agencies.

Health hazards:

Eye Irritation, Category 2B

Skin Sensitization, Category 1

Physical hazards:

Flammable Aerosols, Category 1

Gases Under Pressure

Simple Asphyxiants, Category 1

Label elements

Hazardous components for labelling:

Calcium petroleum sulfonate



Flame



Gas
cylinder



Exclamation
mark

Signal Word: DANGER

Hazard statement(s)

H222: Extremely flammable aerosol.

1043 RUST CHECK RUST INHIBITOR, aerosol

H280: Contains gas under pressure; may explode if heated.

H320: Causes eye irritation.

H317: May cause an allergic skin reaction.

H600: May displace oxygen and cause rapid suffocation.

Precautionary statement(s)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P264: Wash hands thoroughly after handling.

P261: Avoid breathing mist, vapours or spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves and eye protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

Storage:

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

Hazards Not Otherwise Classified: No data available.

Emergency Overview

Immediate concerns: Extremely flammable aerosol. Causes eye irritation. Prolonged and repeated skin contact may lead to slight transient irritation in sensitive individuals. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Inhalation of oil mists may cause irritation of the upper respiratory tract. Oily deposits in the lungs may lead to pulmonary fibrosis and reduced pulmonary function. Vapor reduces oxygen availability for breathing.

Comments: See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial / professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS number
Solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	55 - 59	64742-65-0
Propane	16 - 17	74-98-6

1043 RUST CHECK RUST INHIBITOR, aerosol

Isobutane	7 - 8	75-28-5
Solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	5 - 9	64741-88-4
Mineral oils (petroleum) (non-hazardous ingredient)	3 - 7	8042-47-5
Calcium petroleum sulfonate	3 - 7	61789-86-4
Mineral spirits	1.5 - 2.5	8052-41-3

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

4. FIRST AID MEASURES

Eye Contact: Thoroughly flush the eyes with large amounts of clean water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

Ingestion: Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

Inhalation: If affected by inhalation of spray mist, move to fresh air. Get medical attention if symptoms persist.

Signs and Symptoms of Overexposure

Eye Contact: Mildly irritating to the eyes. Prolonged and repeated contact with the eyes may produce a slight transient irritation. Symptoms may include tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin Contact: Substance does not generally irritate and is only mildly irritating to the skin. Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne. Symptoms may include redness, edema, drying and cracking of the skin. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Ingestion: May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

Inhalation: High spray mist concentrations may be harmful if inhaled. Avoid breathing mists. Inhalation of oil mists may cause irritation of the upper respiratory tract. Oily deposits in the lungs may lead to pulmonary fibrosis and reduced pulmonary function. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

Notes to Physician: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Additional Information: No data available.

5. FIRE FIGHTING MEASURES

Flammable Properties: Extremely flammable aerosol. Can readily form explosive mixtures at or above the flash point. Product can be ignited by static discharge.

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Hazardous Combustion Products: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Fire Fighting Procedures: Containers can build up pressure if exposed to heat (fire).

Fire Fighting Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand,

1043 RUST CHECK RUST INHIBITOR, aerosol

(MSHA/NIOSH approved or equivalent) and full protective gear.

Sensitivity to Static Discharge: Product is sensitive to static discharge.

Sensitivity to Mechanical Impact: Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120 °F (49 °C).

6. ACCIDENTAL RELEASE MEASURES

Small Spill: Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

Environmental Precautions

Water Spill: Do not flush to sewer.

Land Spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Special Protective Equipment: Clean up spills immediately, observing precautions in Protective Equipment section 8.

7. HANDLING AND STORAGE

General Procedures: Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids. Ensure thorough ventilation of stores and work areas.

Handling: Contents under pressure. Do not expose to heat or store above 120 °F (49 °C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breath vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage: Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

OSHA / WHMIS 2015 HAZARDOUS COMPONENTS				
Chemical Name	Occupational Exposure Limits			
	Type		ppm	mg/m ³
Solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	OSHA PEL	TWA	-- [1]	5 [1]
	ACGIH TLV	TWA	-- [1]	5 [1]
	NIOSH REL	TWA	-- [1]	5 [1]
		STEL	-- [1]	10 [1]
Propane	OSHA PEL	TWA	1000	1800
	ACGIH TLV	TWA	1000	--
	NIOSH REL	TWA	1000	1800
Isobutane	ACGIH TLV	STEL	1000	--
	NIOSH REL	TWA	800	1900
Solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	OSHA PEL	TWA	-- [1]	5 [1]
	ACGIH TLV	TWA	-- [1]	5 [1]
	NIOSH REL	TWA	-- [1]	5 [1]
		STEL	-- [1]	10 [1]
Calcium petroleum sulfonate	USA OEL	-	[2]	[2]
Mineral spirits	OSHA PEL	TWA	500	2900
	ACGIH TLV	TWA	100	572
Footnotes:				
1. Oil mist, mineral				
2. This material does not have established exposure limits in the USA under OSHA, NIOSH, ACGIH.				

Engineering Controls: If user operations generate mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Avoid breathing mists; if general ventilation or local exhaust is inadequate, persons exposed to mists should wear approved breathing devices.

Personal Protective Equipment

Eyes and Face: Wear safety glasses with side shields (or goggles).

Skin Contact: Wear chemical resistant gloves. Avoid prolonged or repeated contact with skin.

Respiratory: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protective Clothing: Not applicable for aerosol containers.

Work Hygienic Practices: Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : Liquid, without aerosol propellants

Odor : Characteristic

Odor Threshold : No data available.

Appearance : Aerosol

1043 RUST CHECK RUST INHIBITOR, aerosol

Color	: Red
pH	: Not Applicable
% Volatiles	: 26 - 27% w/w
Flash Point and Method	: > 44°C(111°F) Closed Cup [lowest known value of aerosol concentrate]
Flammable Limits	: 0.9 to 7
Autoignition Temperature	: No data available.
Vapor Pressure	: 55 - 75 psig at 20°C
Vapor Density	: > 1 (air = 1)
Boiling Point	: No data available.
Freezing Point	: No data available.
Melting Point	: No data available.
Solubility in Water	: Practically insoluble
Evaporation Rate (n-butyl acetate = 1)	: > 1
Density	: 0.84-0.90 g/ml at 20°C

Notes: An estimate for the aerosol concentrate density.

Viscosity	: 120 to 160 cSt at 23°C
VOC Content	: 26 - 27% w/w
Oxidizing Properties	: None

Comments:

Flammability Statement:

The flammability of an aerosol is determined by its flame extension and/or flashback.

Flammability:	Yes
Aerosol Flame Projection:	>15 cm but <100 cm
Flashback:	None
Calculated Aerosol Chemical Heat of Combustion, kJ/g	31 to 35

VOC Compliance Statement

Total Volatiles:	26 - 27% w/w
VOC Content:	26 - 27% w/w, less exempts Product-Weighted Reactivity (PWR): 0.55 to 0.59 g O ₃ /g product

VOC Regulation: USA National VOC Emission Standards for Aerosol Coatings
- 40CFR PART 59 SUBPART E
Coating Category: Flat Coating Product
**The VOC content meets the 1.20 PWR category limit for Flat Coating Product.
USA compliant.**

VOC Regulation: CARB-California - Consumer Product Regulations
Product Category: Rust Preventative Lubricant, aerosol
**The product VOC content does not meet the current 25% w/w limit under the CARB
Consumer Product Regulations for Rust Preventative Lubricant, aerosol.
Not for sale in California.**

1043 RUST CHECK RUST INHIBITOR, aerosol

VOC Regulation: UT, LADCO & OTC States - Consumer Product Regulations

Product Category: Multi-Purpose Lubricant

The product VOC content meets the current 50% w/w limit under the above Consumer Product Regulations for Multi-Purpose Lubricant. Compliant for sale in UT, IL, IN, MI, OH and the OTC states.

Check your area for compliance before using this product.

10. STABILITY AND REACTIVITY

Reactive Hazard : No

Hazardous Polymerization: Not expected to occur.

Stability: Stable.

Conditions to Avoid: Keep away from flames and any object that sparks. Container may explode if heated.

Possibility of Hazardous Reactions: No data available.

Hazardous Decomposition Products: Carbon Monoxide and other toxic vapors.

Incompatible Materials: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Chemical Name	Oral LD ₅₀ mg/kg (rat)	Dermal LD ₅₀ mg/kg (rabbit)	Inhalation LC ₅₀ mg/l
Solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	> 5000	> 5000	>5.0(rat;4h - mist)
Propane	Not Applicable	Not Applicable	>800,000 ppm (rat,15m) [>1443 mg/L]
Isobutane	Not Applicable	Not Applicable	658(rat;4h) 570,000 ppm (rat;15m) 680(mouse;2h)
Solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	> 5000	> 5000	>5.0(rat;4h - mist)
Calcium petroleum sulfonate	> 2000	> 2000	No data available.
Mineral spirits	> 5000	> 3000	8.5(rat;8h) >5.5(rat;4h)

Acute Toxicity - Dermal LD₅₀: Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

Acute Toxicity - Oral LD₅₀: Based on available ingredient data, the classification criteria for Acute Oral Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

Acute Toxicity - Inhalation LC₅₀: Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture. The calculated ATE is >20 mg/l/4h (vapours) and >5 mg/l/4h (mists).

Notes: < 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity. No additional toxicology information is available for this product itself. (See Component Toxicity Information).

1043 RUST CHECK RUST INHIBITOR, aerosol

Skin Irritation / Corrosion: Based on available data, the classification criteria for skin irritation are not met for this mixture. Substance does not generally irritate and is only mildly irritating to the skin. Prolonged contact with this product may cause an allergic skin reaction. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

Eye Irritation / Serious Eye Damage: The mixture is classified as: Eye Irritant, category 2B, based on ingredient data. Causes eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Respiratory / Skin Sensitizer: Contains: Calcium petroleum sulfonate. May cause sensitization by skin contact. The mixture is classified as: Skin Sensitizer, category 1 based on ingredient data ($\geq 0.1\%$ ingredients classified as a skin sensitizer, category 1 or sub-category 1A or $\geq 1.0\%$ ingredients classified as a skin sensitizer, sub-category 1B). Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Based on available data, the classification criteria for respiratory sensitization are not met for this mixture ($< 0.1\%$ ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and $< 1.0\%$ ingredients classified as a respiratory sensitizer, sub-category 1B).

Germ Cell Mutagenicity: Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture ($< 0.1\%$ ingredients classified as Germ Cell Mutagen, category 1A or 1B and $< 1.0\%$ ingredients classified as Germ Cell Mutagen, category 2).

Carcinogenicity

Chemical Name	NTP status	IARC status	OSHA status	Other
Solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	--	--	--	--
Propane	--	--	--	--
Isobutane	--	--	--	--
Solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	--	--	--	--
Calcium petroleum sulfonate	--	--	--	--
Mineral spirits	--	--	--	--

Notes: The mineral oils in this product are highly refined. Based on available data, the classification criteria for Carcinogenicity are not met for this mixture ($< 0.1\%$ ingredients classified as a Carcinogen, category 1 or 2). The mineral oils in this product are highly refined and are classified: Inadequate evidence for carcinogenicity of highly refined oils - IARC 1987. This product is formulated with mineral oils containing $< 3\%$ w/w extractables for total polycyclic aromatic compounds (PAC) as measured using IP 346.

Reproductive Toxicity: Based on available data, the classification criteria for Reproductive Toxicity are not met for this mixture ($< 0.1\%$ ingredients classified as Reproductive Toxicity, category 1 or 2).

Specific Target Organ Toxicity - Single Exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Single Exposure are not met for this mixture ($< 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 1 or 2 and $< 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3).

Specific Target Organ Toxicity - Repeated Exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Repeated Exposure are not met for this mixture ($< 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 1 or 2).

Aspiration Hazard: Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ($< 10\%$ ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm²/s at 40 °C).

12. ECOLOGICAL INFORMATION

Environmental Data: No data available.

1043 RUST CHECK RUST INHIBITOR, aerosol

Ecotoxicological Information: No data available.

Bioaccumulation/Accumulation: No data available.

Distribution: No data available.

Aquatic Toxicity (Acute): No data available.

Chemical Fate Information: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

Product Disposal: When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

14. TRANSPORT INFORMATION

DOT (Department of Transportation)

Proper Shipping Name : Aerosols, Flammable

Primary Hazard Class/Division: 2.1

UN/NA Number : 1950

Packing Group : N/AP

Other Shipping Information:

With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity as per DOT 173.306.

Vessel (IMO/IMDG)

Shipping Name : Aerosols

UN/NA Number : 1950

Primary Hazard Class/Division: 2.1

Packing Group : N/AP

Marine Pollutant : None

Label : None

Note: With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

Canadian Transportation of Dangerous Goods Regulations

Shipping Name : Aerosols, Flammable

UN/NA Number : 1950

Primary Hazard Class/Division: 2.1

Packing Group : N/AP

TDG Note:

With an inner packaging < 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

15. REGULATORY INFORMATION

UNITED STATES

SARA Section 311/312 Hazard Categories

311/312 HEALTH HAZARDS: Eye Irritation, Simple Asphyxiants, Skin Sensitization

311/312 Physical Hazards: Flammable Aerosols, Gases Under Pressure

EPCRA Section 313 Toxic Chemicals:

This product does not contain any listed toxic chemicals that exceed the threshold reporting levels established by SARA Title III, Section 313.

EPCRA Section 302 Extremely Hazardous Substances

EPCRA Status:

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

CERCLA Status:

This product contains no CERCLA listed hazardous substances.

TSCA (The Toxic Substances Control Act)

TSCA Status:

All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112(b) - Hazardous Air Pollutants

CAA 112(r) - List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(b).

This product contains the following chemicals subject to CAA 112(r).

Name	CAS No.	Threshold Qty (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

California Proposition 65:

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

CANADA

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

1043 RUST CHECK RUST INHIBITOR, aerosol

Name	CAS No.	NPRI Part No.
Stoddard solvent	8052-41-3	5 (VOC)
Propane	74-98-6	5 (VOC)
Butane (all isomers)	75-28-5	5 (VOC)

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

Comments VOC Content -- See section 9.

16. OTHER INFORMATION

Reason for Issue: The Safety Data Sheet was updated.

Approved By: Jim Gordon **Title:** R&D Chemist

Prepared By : Regulatory Compliance


Date Revised: 11/18/2019

Information Contact: 905-670-5411

Revision Summary: This MSDS replaces the 11/18/2019 MSDS.

HMIS RATING

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		0
PERSONAL PROTECTION		E

NFPA CODES

NFPA 30 / 30B Storage Classification: Level 3 Aerosol

Manufacturer Supplemental Notes: None

Data Sources: Not Available

Additional SDS Information:

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Administration

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

General Statements: None

Comments: None

Manufacturer Disclaimer: The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.